



The Communication Stack Solution
for the Software-Defined Vehicle

Zetta Auto is the unified solution for in-vehicle and V2X communication for the automotive market by TTTech Auto and ZettaScale.

Targeting data-centric architectures and support for service-oriented architectures (SOA), for in-vehicle communication, Zetta Auto builds upon ZettaScale's open core Eclipse Cyclone DDS, a proven, performant, interoperable, scalable and real-time capable implementation of OMG Data Distribution Service (DDS) and *Eclipse Zenoh*, a next generation pub/sub/query protocol with incredible high performance and scalability as well as exceptionally low resource usage.

Zetta Auto extends these core technologies with automotive features such as integration with Time Sensitive Networking (TSN) to provide end-to-end communication properties and compatibility with AUTOSAR Classic RTE communication on Microcontrollers (MCUs).

It also comes with an integrated tool suite that enables users to configure and monitor communication data as well as their TSN network. Zetta Auto Certified will furthermore offer an ISO 26262 ASIL-D certified version of the in-vehicle stack.

Looking beyond the vehicle, customers currently find it technically challenging communicating and managing data in the cloud-to-microcontroller continuum. This is due to the diverse set of environments, requirements, and technical solutions. Thanks to the interoperability with the *Zetta Platform*, Zetta Auto will make it possible to seamlessly manage and communicate data between the cloud and the vehicle.

ZETTA AUTO USPs



Suitable for prototype and production systems, enabling seamless transition between development phases



ISO26262 ASIL-D certification in progress



Top performance with optimal resource usage for Microcontrollers



Open source foundation with a path towards safety certification



End-to-end timing properties with Time Sensitive Networking (TSN) integration



Integrated tool suite for DDS and TSN



Unified communication for the Software-Defined Vehicle, in-vehicle and V2X.

HIGHLIGHT PRODUCT FEATURES

In-vehicle communication stack

Data-centric communication for the automotive industry

- Build your in-vehicle communication stack on a standards-based solution compliant with: OMG DDS v1.4, OMG IDL4 v4.2 and OMG DDS-RTPS v2.5 specifications.
- Brings developers a best-in-class user experience with C, C++ and Python APIs.
- High performance zero-copy shared memory management, fully abstracted for the user.
- Broad automotive ecosystems support across operating systems (Linux, QNX, Android) and automotive middlewares: MotionWise – TTTech Auto's Safety Middleware, ROS2 and AUTOSAR Adaptive.

Built together with TSN for end-to-end predictable communication

- Zetta Auto leverages TSN (IEEE 802.1Qbv Time Aware Shaping) and unleashes both DDS and TSN to achieve communication timing properties.
- Includes end-to-end tool for the configuration of TSN networks, topology design, traffic scheduling and deployment of the result.

Resource-efficient and performant microcontroller solution with Zenoh Pico

- Optimized MCU stack and integrated tooling that enables access to DDS topics through AUTOSAR Classic RTE.
- Minimal resource usage and optimal performance in comparison to XRCE-DDS implementations for resource-constrained environments.

V2X communication stack

Pub/sub/query from cloud-to- vehicle

- Built on Zenoh protocol, Zetta Platform and fully integrated with Cyclone DDS.
- Unified data in motion, data at rest and computations from microcontrollers up to the data center.
- Location-transparent abstractions for high performance pub/sub and distributed queries across heterogeneous systems.
- Supports a continuously expanding set of Protocol and Storage plug-ins, such as MQTT, REST and a variety of storage providers.

Tool Suite

Monitor, configure and test your network with ZettaC2

- Provides a dashboard to capture the Key DDS computational entity, Data & metadata they exchange and their QoSs.
- Detects QoS conflicts, datatype, and configuration mismatches.
- Provides System-wide view of the network topology and helps making health monitoring.
- Operates in headless and GUI based mode from any place in the network.
- Measurement tool for key performance indicators such as latency, throughput and roundtrip time in your own system.

NOTABLE FEATURES OF THE DDS STACK

FEATURE	AVAILABLE	DESCRIPTION
API <ul style="list-style-type: none"> C C++ Python 	Yes Yes Yes	<ul style="list-style-type: none"> DDS APIs in C, C++ or Python
LARGE DATA SUPPORT <ul style="list-style-type: none"> Async publication 	Yes	<ul style="list-style-type: none"> The Application Writing thread is decoupled from the DDS sending thread Ability to protect data topics, DDS partitions, DDS domains with Read/Write access controls
SECURITY <ul style="list-style-type: none"> Authentication Access control Message encryption Message authentication 	Yes Yes Yes Yes	<ul style="list-style-type: none"> Cryptography uses AES-GCM and AES-GMAC for message authentication The ability to check application identity and/or that invokes operations on DDS
DDS XTYPES 1.3	Yes	<ul style="list-style-type: none"> Ability to evolve data type definition while maintaining backward compatibility with old versions
DYNAMIC DISCOVERY	Yes	<ul style="list-style-type: none"> Ability to automatically discover new DDS entities in the system at runtime
TIME SENSITIVE NETWORK <ul style="list-style-type: none"> Qbv (scheduled traffic) Simplified configuration 	Yes	<ul style="list-style-type: none"> Ability to synchronise Cyclone writing and reading thread with the overall end to end scheduling VLAN tagging in the DDS stack without OS dependencies
ASIL ZERO-COPY SHARED MEMORY IPC	Roadmap QM available	<ul style="list-style-type: none"> Ability to share data by exchanging pointers instead of content
STATIC DISCOVERY	Roadmap	<ul style="list-style-type: none"> Static discovery mechanism

DDS STACK QOS SUPPORT

QUALITY OF SERVICE (QOS)	SUPPORTED	QUALITY OF SERVICE (QOS)	SUPPORTED
USER DATA	Yes	OWNERSHIP STRENGTH	Yes
TOPIC DATA	Yes	LIVELINESS	Yes
GROUP DATA	Yes	TIME BASED FILTER	Yes
DURABILITY		PARTITION	Yes
<ul style="list-style-type: none"> Volatile 	Yes	RELIABILITY	Yes
<ul style="list-style-type: none"> Transient-local 	Yes	TRANSPORT PRIORITY	Yes (default)
<ul style="list-style-type: none"> Transient 	(Roadmap)	LIFESPAN	Yes
<ul style="list-style-type: none"> Persistent 	(Roadmap)	DESTINATION ORDER	Yes
DURABILITY SERVICE		HISTORY	Yes
<ul style="list-style-type: none"> Cleanup Delay 	(Roadmap)	RESOURCE LIMITS	Yes
<ul style="list-style-type: none"> History 	Yes	ENTITY FACTORY	(On customer demand)
<ul style="list-style-type: none"> Resource limits 	(Roadmap)	WRITER DATA LIFECYCLE	(Roadmap)
PRESENTATION	No	READER DATA LIFECYCLE	(Roadmap)
DEADLINE	Yes		
LATENCY BUDGET	Yes		
OWNERSHIP	Yes		

DELIVERY PACKAGE

In-Vehicle DDS Stack

- Zetta Auto DDS stack binaries for Linux, QNX and Android on ARM. (Source code delivery option available)
- IDL compilers for C, C++ and Python
- User Manual for Application Developers and System Integrators

In-Vehicle MCU Stack

- Complex Device Driver binaries incl. gateway and gateway API for mapping between RTE and DDS communication. (Source code delivery option available)
- Generators for gateway and model integration
- Zenoh Pico binaries. (Source code delivery option available)
- Integration Manual for AUTOSAR Classic
- Zenoh transport plugin for DDS stack

DDS + Zenoh Tooling

- ZettaC2
- ZettaC2 User Manual